


Product data sheet

FLAT POLYMERO

311627.002.8.19

RZB




IP
40

IK
03

Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface). With integrated HF movement sensor. Functional parameters of the motion detector (ceiling mounting up to 4.0 m or wall mounting up to 2.7 m): HF detector 5.8 GHz ISM frequency band. Sensitivity/Range: 1-8 m in diameter, adjustable from 20-100%. Time control between 10 seconds and 30 minutes, adjustable. Coverage: 120°. Can be used as master luminaire up to 800 W (ohmic load), 500 W (fluorescent lamp, LED) / 400 A, 200 µs. Suitable for outdoor use to a limited extent only, due to sensitive reaction to all movements. Colour: white Diameter: 300 mm Height: 100 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 14 W Rated luminous flux: 1500 lm Beam angle Down: 119° Luminous efficiency: 107 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14 W	CRI	80
Total flux	1500 lm	LOR	67%
Luminous efficacy	107 lm/W	ULOR	17%
		Total power	14 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.94 in

Diameter: 11.81 in

Adjustability

Fixed

Electric

System power: 14 W

Protection

IP: 40

IK: 03