# Product data sheet

PRUNUS-D2-PA05-32LED-3000K-3500LM-21.3W

LIGHTRONICS



IP 66 IK 10

PRUNUS D DESIGN WITH AN EYE FOR DETAIL The main characteristic of the PRUNUS is that this luminaire provides light where and when required. The PRUNUS D is a round hanging luminaire with four different diffusers. This street and yard lighting can be fitted with a coupling piece for attachment to overhead cables. The luminaire is suitable for business parks, public squares and parks, town and village centres and residential areas. The options include various colour temperatures and an RGB LED ring. The Prunus D is waterproof (IP66) and impact-resistant (IK10).

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 21.3 W | CRI | 70 |
| Total flux | 94 lm | LOR | 87% |
| Luminous efficacy | 4 lm/W | Total power | 21.3 W |

### Mounting mode

Pendant, Ceiling mounted

### Shape and measurements

Height: 3.94 in

Diameter: 19.69 in

### Adjustability

Fixed

### Design

Material impression: Aluminum

Color of housing: Anthracite / graphite

### Electric

System power: 21.3 W

### Protection

IP: 66

IK: 10