

# Product data sheet

ROUNDED SUPERFLACH  
581608.0031.19  
RZB




IP  
66

IK  
10

Series: Rounded Superflach Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 50 Hz Pressure die-cast housing of corrosion resistant Aluminium, powder coated, flat diffuser of opal polycarbonate with fixing clamps, drill hole deviations can be compensated, with second cable entry for loop-through, integral HF motion-sensor switch. Available Colours: anthracite metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 268, H 70 Lamp: LED Life time: 45000 h (L70/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 390lm System power: 8,5W Beam Angle: 115° Unified Glare Ratio: 19,2 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.5 W	CRI	80
Total flux	390 lm	LOR	100%
Luminous efficacy	46 lm/W	Total power	8.5 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.94 in  
Diameter: 10.55 in

## Adjustability

Fixed

## Electric

System power: 8.5 W

## Protection

IP: 66  
IK: 10