## Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, LENS WALLWASHER AF1105105-33-40 24W

SCHMITZ | WILA








alphabet focus LED 4000 K Recessed Luminaire, Light distribution direct, asymmetric Wallwasher Lens Wallwasher Product: AF1105105-33-40 Operating technology: independent driver required Lens wall washer create a uniform illumination on vertical surfaces without any hard shadow. Room proportions can be perfectly emphasized thanks to a harmonious brightness distribution. Light Technique asymmetric light distribution highly precise optical system, combining primary focus lens and secondary light control lens CRI > 90 constant colour temperature 4000K chromaticity stability with <3SDCM lifetime 50.000 h (L70) aluminium reflector (Al99.98), high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2mm for homogeneous appearance in the ceiling ring colour white, RAL9016 Operating and assembly technology Order LED gear box separately Gear boxes suitable for connection to central battery systems Quick installation due to 4-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 24 W Colour Rendering Index: 90 Colour Temperature: 4000 K Luminaire Luminous Flux: 1520 Llm System Efficiency: 56 Llm/W Number Luminaires LZ: 0.09 Connector: Screw Connector, 3 x 1.5 mm2 Reflector Size: R15 Diameter D: 172 mm Cut-out CO: 165 mm Overhang OH: 145 mm Installation Depth RD: 200 mm Total Weight: 1.6 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF1105105-33-40\_24W

## Light output 1



1 x General	service	incand	lescent	lamn
I A Octiciai	oci vioc	mound	COOCIIC	iuiip

Nominal lamp power	27 W
Lamp flux	1520 lm
Luminous efficacy	56 lm/W
CCT	4000 K
CRI	90

LOR 100%
Total flux 1520 lm
Total power 27 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 7.87 in Diameter: 6.77 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 27 W Appliance Class: II

Protection

IP: 20