

Product data sheet

STREET LIGHTING
V1-S1-90441-40T32-6612040 TORNADO XTREM ROAD 120W 4000K
VARTON




IP
66

IK
09

LED street light luminaire. Tool-free access to the driver. Adjustable spigot. Cast aluminum housing, tempered protective glass. Application: roads and streets (low temperature regions). Installation: pole and side-entry mounted (Ø48mm-60mm). Power factor: 0,97 Rated ambient temperature according to IEC62722-2-1, °C: -60...45 AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: YXL1 Color rendering index: 70-79 Protection class: I Suitable for top end size, mm: 48...60 Mounting method: Side-entry Ingress protection (IP): IP66 Impact resistance: IK09 Nominal voltage, V: 220...230 <https://www.varton.ru/products/ulichnoe-osveshchenie/tornado/tornado-xtrem-road-dlya-dorogi/svetodiodnyy-svetilnik-var-ton-ulichnyy-konsolnyy-tornado-xtrem-road-120-vt-4000-k-ra19005-chernyy-mu/>

Light output 1



1 x LED			
Nominal lamp power	120 W	LOR	100%
Lamp flux	16200 lm	Total flux	16200 lm
Luminous efficacy	135 lm/W	Total power	120 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 28.35 in
Width: 12.20 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 120 W

Protection

IP: 66
IK: 09