# Product data sheet


QUADRO OFFICESPECIAL SUSPENSION DI/ID SILVER VDT 3
T65H33X-9006C2940L1B
PLANLICHT



IP 20


LED LO 4000K 46W 6077lm CRI90 https://katalog.planlicht.com/en-gb/fam-quadro/

## Light output 1 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 11.5 W | CRI | 90 |
| Total flux | 1519 lm | LOR | 100% |
| Luminous efficacy | 132 lm/W | ULOR | 34% |
| | | Total power | 11.5 W |

## Light output 2 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 11.5 W | CRI | 90 |
| Total flux | 1519 lm | LOR | 100% |
| Luminous efficacy | 132 lm/W | ULOR | 34% |
| | | Total power | 11.5 W |

## Light output 3 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 11.5 W | CRI | 90 |
| Total flux | 1519 lm | LOR | 100% |
| Luminous efficacy | 132 lm/W | ULOR | 34% |
| | | Total power | 11.5 W |

## Light output 4 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 11.5 W | CRI | 90 |
| Total flux | 1519 lm | LOR | 100% |
| Luminous efficacy | 132 lm/W | ULOR | 34% |
| | | Total power | 11.5 W |

### Mounting mode

Pendant

### Shape and measurements

Length: 1.97 in
Width: 132.48 in
Height: 2.60 in

### Adjustability

Fixed

### Electric

System power: 46 W

### Protection

IP: 20