

# Product data sheet

CLOSS LED DIRECT WHITE 1200 BETA OPTI 4K CLO  
12160-516  
FAGERHULT



Installation Surface mounted or wire suspension. Installation via wire suspension requires wire brackets which provide flexible c/c, see accessories. Luminaires for wire suspension need a counterbalance (wire suspension and counter-balance, ordered separately). Connection Three Ø 19 mm cable entries fitted with blanking grommets on the top of the luminaire, see dimension chart. Knock-outs at each end for surface mounted mains cable. 3-way snap-in terminal block in the centre of the luminaire. Luminaires for dimming, 5-way snap-in terminal block, 1-phase through-wiring possible. Design Luminaire body in sheet steel and end-caps of die-cast aluminium in a white (RAL 9016) structured or alu-grey (RAL 9006) structured finish. Louvre Beta Opti – double parabolic reflector louvre with satin matt metallised aluminium side and cross-blades with an integrated opal film that minimises the risk of uncomfortable glare from the diodes. Reflector The louvre acts as a reflector.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	22 W	CRI	80
Total flux	2903 lm	LOR	100%
Luminous efficacy	132 lm/W	Total power	22 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 47.91 in  
Width: 4.92 in  
Height: 2.17 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray, White

## Electric

System power: 22 W

## Protection

IP: 20