


Product data sheet

ALU-SUPERIOR
51050.004
RZB




IP
65

IK
08

Series: Alu-Superior Type of Protection: IP 65 Protection Class: I Voltage: - 250 / 0 - 60 Hz Base and bezel ring: die-cast aluminium, powder-coated. Diffuser: plastic (polycarbonate), opal. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 245, H 120 Lamp: 1 x QA60 (klar) max. 57 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK08 (5 Joule) Beam Angle: 134° Unified Glare Ratio: 18,7 EEC: A++ - E

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	57 W	Socket	E27
Lamp flux	915 lm	LOR	49%
Luminous efficacy	8 lm/W	ULOR	6%
CCT	3000 K	Total flux	447 lm
CRI	90	Total power	57 W

Mounting mode

Wall mounted

Shape and measurements

Height: 4.72 in
Diameter: 9.65 in

Adjustability

Fixed

Electric

System power: 57 W

Protection

IP: 65
IK: 08