Product data sheet

O35 LED 900 830 1000MM

GLAMOX



IP 65 IK 07

Light source LED 900 - 1500 lumen out Colour temperature 4000 K, CRI Ra 80, MacAdams 3 On request: 3000 K Driver Fixed output (HF). Body material & colour Housing in extruded and die-cast aluminium. A first layer of epoxy powder and a second layer of polyester powder coated paint finish. Black (close to RAL 9005), aluminium grey (close to RAL 9006) or anthracite (close to RAL 7043). Clear polycarbonate diffuser. Silicone gasket. Stainless steel screws. Mounting Mounted to a root column that has to be ordered separately or directly to fixed base. Accessories Root column. Connection Supplied with IP68 connector and pre-assembled 2x0,75 mm² cable.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	80
Total flux	860 lm	LOR	100%
Luminous efficacy	51 lm/W	ULOR	84%
		Total power	17 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 5.91 in

Diameter: 5.91 in

Adjustability

Fixed

Design

Color of housing: Black, Anthracite / graphite, Silver gray

Electric

System power: 17 W

Appliance Class: II

Protection

IP: 65

IK: 07