Product data sheet

GEORG V (1-ARMED) 9.870.0127.04

LEIPZIGER LEUCHTEN






CRI




With mounting heights between 3.00 and 4.00 m for medium and low light requirements. - Large shade, inside in special white paint for better reflection - Luminaire body made of aluminium/galvanized steel sheet, outside painted in colour, inside finished in special white pain - Impactresistant polyethylene attachment rotates and locks into place for easy lamp replacement - Steel tubing galvanized and painted -Wired ready for connection - Connection by adapter jack -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm,and pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 54 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp			
Nominal lamp power	125 W		
Lamp flux	6800 lm		
Luminous efficacy	36 lm/W		
CCT	3400 K		

LOR 72% UI OR 4% Total flux 4887 lm Total power 137 W



1 x High pressure mercury vapour lamp

5 1	, , ,		
Nominal lamp power	80 W	LOR	72%
Lamp flux	4000 lm	ULOR	4%
Luminous efficacy	32 lm/W	Total flux	2875 lm
CCT	3400 K	Total power	89 W
CRI	54		

54

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in Diameter: 22.83 in Electric

System power: 89-137 W

Protection

IP: 54