



Product data sheet

AMES L30 *O MET LE3
AMENITY PLUS METAL - SQUARE EMERGENCY
DEXTRA




Amenity Plus Metal - IP65, IK10. Square surface mounted luminaire with white or black alumainm base and opal diffuser. Installation options include BESA box or direct surface mount with conduit side or rear cable entry. Options: LE3 - Lithium Emergency (194 lumens) LS3 - Lithium Selftest LA3 - Lithium Autotest A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* S - Switch Dimming D - Digital Dimming (DSI) R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode* RLM - Reacta-Link Wireless Microwave Presence & Bright Out RCME - Reacta-Control Wireless Microwave On/Off RCMC - Reacta-Control Wireless Microwave Corridor Mode* *Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off. PH - Photocell (Dawn to Dusk switching photocell) WO - White Body BO - Black Body

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	22.4 W	CRI	80
Total flux	1794 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	6%
		Total power	22.4 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.5 W	CRI	80
Total flux	194 lm	LOR	100%
Luminous efficacy	55 lm/W	ULOR	6%
		Total power	3.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 12.60 in

Width: 12.60 in

Height: 4.09 in

Electric

System power: 25.9 W

Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 65

Designation labels: CE