Product data sheet

LOUI BEAMLINE
921600.0045.1.76
RZB



IP 20 IK 03

Series: LESS IS MORE BEAMLINE system Colour: silver, matt (approx. RAL 9006) Length: 2242 mm Width: 57 mm Height: 75 mm Suspension length: 600-2000 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 90 Light source: LED Socket lamp2: Without base Colour temperature: 4000K System power: 76 W Rated luminous flux: 7700 lm Beam angle Down: 8° Luminous efficiency: 101 lm/W Control gear: Converter, dimmable, DALI Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	90
Total flux	1925 lm	LOR	67%
Luminous efficacy	101 lm/W	ULOR	14%
		Total power	19 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	90
Total flux	1925 lm	LOR	67%
Luminous efficacy	101 lm/W	ULOR	14%
		Total power	19 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	90
Total flux	1925 lm	LOR	67%
Luminous efficacy	101 lm/W	ULOR	14%
		Total power	19 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	90
Total flux	1925 lm	LOR	67%
Luminous efficacy	101 lm/W	ULOR	14%
		Total power	19 W

Mounting mode

Pendant

Shape and measurements

Length: 2.24 in
Width: 88.27 in
Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 76 W

Protection

IP: 20
IK: 03