


Product data sheet

X-LINE SLIGHT SPOTS LOW UGR L-DOWN LED 1800 LOUVER EDD / 2X 600 15° EDD 34 830 / L-1200MM S-1,5M TWO CIRC..
19.4400.111F.34
LUXIONA



Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 1200 x 34 x 68 mm. Diffuser: LOUVER (anti-glare louver) / optical system based on PMMA lenses. The efficiency of the optical system is 71,66%. Beam angle: (C0-C180) / (C90-C270) - 46° / 44,6° // (C0-C180) / (C90-C270) - 17,8° / 19,8°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 1269 / 1020 lm. Power of luminaire: 10,8 / 10,8 W. Luminaire's light efficiency: 117,5 / 94,4 lm/W. Driver: DIM DALI (EDD) / DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Circuit load capacity: 7 (B10), 12 (B16), 11 (C10), 18 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



3 x LED			
Nominal lamp power	3.6 W	LOR	52%
Lamp flux	591 lm	Total flux	930 lm
Luminous efficacy	164 lm/W	Total power	10.8 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 47.24 in

Width: 1.34 in

Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10.8 W

Controller: DALI

Appliance Class: I

Protection

IP: 40

IK: 04

Other operating numbers

Ambient temperature range: 41...95°F