



Product data sheet

FLAT BASIC
211425.002.1
RZB



Series: Flat Basic Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: plastic. Diffuser fastening: bayonet lock. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 630, H 160 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2800lm System power: 33W Beam Angle: 117° Number of fittings B10A: 53 Number of fittings B16A: 85 Number of fittings C10A: 53 Number of fittings C16A: 85 Inrush current: 0,2A Unified Glare Ratio: 17,8 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	33 W	CRI	80
Total flux	2800 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	16%
		Total power	33 W

Mounting mode

Wall mounted

Shape and measurements

Height: 6.30 in

Diameter: 24.80 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 33 W

Protection

IP: 43

IK: 03