


Product data sheet

ZAAB 2 CLUSTER COLUMN PROJECTORS
ZA-20001-M-W40-A52731
LIGMAN




- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear installed in the spigot cover post top

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	2128 lm	LOR	100%
Luminous efficacy	54 lm/W	Total power	39.3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	2128 lm	LOR	100%
Luminous efficacy	54 lm/W	Total power	39.3 W

Light output 3 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	2128 lm	LOR	100%
Luminous efficacy	54 lm/W	Total power	39.3 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 18.39 in

Width: 6.10 in

Height: 216.54 in

Weight: 36.8 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 117.9 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 66

IK: 07

Surface temperature: 40°C