


Product data sheet

CALLISTO POLE BLACK 60LM 2700K RA>80 TRAILING EDGE DIMMING
7021989141075
SG ARMATUREN



Attractive garden lamp for outdoor use. Well integrated LED chip, dimmable via phase-dimming. Made of die-cast powder-coated aluminium, powder coating and 10-year corrosion warranty, glass diffuser. 60 cm in total height, direct 230 V with loopable quick clips, front locked using torx. IP44, vandal-resistant. Can be screwed to tile or concrete, and embedded using an anchor (accessory) Light distribution Direct/Asymmetric Light technic LED (not exchangeable) 3W 2700K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP44 Energy and approvals CE Materials and finish Housing: Aluminium Colour: Black (RAL 9004) Optics: Glass Mounting/Connection Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 115, B16: 184, C10: 134, C16: 215

Light output 1



1 x LED			
Nominal lamp power	3 W	LOR	100%
Lamp flux	60 lm	Total flux	60 lm
Luminous efficacy	20 lm/W	Total power	3 W
CCT	2700 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 2.91 in
Width: 6.14 in
Height: 22.64 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 3 W
Appliance Class: I

Protection

IP: 44