

Product data sheet

壁灯

PAK491320 PAK-M26-008C-Y-A


PAK




IP
54

灯 体：采用优质铝合金灯体外壳，表面聚脂喷层处理，耐腐蚀。 防水等级：IP54 适用光源：晶锐系列MR16灯杯（2*4W）适用园林、街道、广场、公园等照明。


Light output 1



1 x LED			
Nominal lamp power	7 W	Socket	G5.3
Lamp flux	360 lm	LOR	100%
Luminous efficacy	90 lm/W	Total flux	360 lm
CCT	4000 K	Total power	4 W
CRI	85		




1 x LED			
Nominal lamp power	4 W	Socket	G5.3
Lamp flux	255 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	255 lm
CCT	4000 K	Total power	4 W
CRI	85		




1 x LED			
Nominal lamp power	4 W	Socket	G5.3
Lamp flux	255 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	255 lm
CCT	3000 K	Total power	4 W
CRI	85		


Light output 2



1 x LED			
Nominal lamp power	7 W	Socket	G5.3
Lamp flux	360 lm	LOR	100%
Luminous efficacy	90 lm/W	Total flux	360 lm
CCT	4000 K	Total power	4 W
CRI	85		



1 x LED			
Nominal lamp power	4 W	Socket	G5.3
Lamp flux	255 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	255 lm
CCT	4000 K	Total power	4 W
CRI	85		



1 x LED			
Nominal lamp power	4 W	Socket	G5.3
Lamp flux	255 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	255 lm
CCT	3000 K	Total power	4 W
CRI	85		

Mounting mode

Wall recessed

Shape and measurements

Length: 2.80 in
Width: 2.74 in
Height: 0.00 in

Adjustability

Fixed

Electric

System power: 8 W

Protection

IP: 54