

Product data sheet


TIBI CEILING/WALL 600 3K
55262-402
FAGERHULT



IP
41

Installation Two securing holes for wall mounting. IP 40. IP 41 is available upon request. Connection Snap-in terminal block 5x2.5 mm², 1-phase through-wiring possible. Cable entry from top of the luminaire. Surface mounted mains cable possible, through-wiring 180°. Design Diffuser in specular opal acrylic. Luminaire body/decorative edge ring in aluminium. Decorative edge ring lacquered in glossy black (RAL 9005) or clear lacquered brushed aluminium. Dimming DALI dimming as standard. e-Sense Detect - microwave sensor for on/off function, or absence dimming with the option of switch-off function. e-Sense Move - wireless control between luminaires. Microwave sensor for the on/off function, or absence dimming with the option of switch-off function. For further information please refer to the dimming section in the Technical chapter.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	80
Total flux	3771 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	13%
		Total power	30 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 6.57 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 30 W

Protection

IP: 41