



Product data sheet

PLEXI_ROUND_RECESSED_620_LED_60W_NEUTRAL_D620MM
82331281
PETRIDIS



An opal frameless circular luminaire with a contemporary design. PLEXI ROUND is a piece of architecture, perfect for adding stature to an area. With it's gentle uniform lighting, it upgrades areas such as lobbies, corridors, offices, stores and homes. It is available in five diameters: 300, 350, 450, 620, 900 and 1200mm. Technical Features - Aluminium body, painted electrostatically in selected colour. - Version with opal plexi glass or microprismatic cover. - Easy installation. - Pure light without IR/UV radiation. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux L80B10). - Connection for operation on 230V/50Hz. Upon Request - Connection for emergency lighting system, for one or three hours.

Light output 1



1 x LED			
Nominal lamp power	60 W	LOR	69%
Lamp flux	10051 lm	Total flux	6941 lm
Luminous efficacy	168 lm/W	Total power	60 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.72 in
Diameter: 23.62 in

Adjustability

Fixed

Design

Material impression: Aluminum, Plastic

Electric

System power: 60 W
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 40
Designation labels: CE