


Product data sheet

ORION WHITE 1350LM 3000K RA>80 SENSOR WIRELESS
7021982121173
SG ARMATUREN



Attractive, round LED wall/ceiling luminaire for indoor mounting. Made of painted metal. Diffuser made of UV-stabilised opal polycarbonate. Efficient LED board with long service life. Hatch for easy access to connection, and option of both visible and concealed cabling as well as loopable quick clips. Vandal-resistant rating IK10. Light distribution Direct Light technic LED 19W 3000K Ra>80 SDCM 3 L70/B10 >50,000 hrs Control/Dimming Sensor Wireless Protection Class II IP20 IK10 Materials and finish Housing: Steel Colour: White Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 35, B16: 56, C10: 43, C16: 69

Light output 1



1 x LED			
Nominal lamp power	19 W	LOR	100%
Lamp flux	1350 lm	ULOR	6%
Luminous efficacy	71 lm/W	Total flux	1350 lm
CCT	3000 K	Total power	19 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.85 in
Width: 11.85 in
Height: 3.43 in

Adjustability

Fixed

Electric

System power: 19 W
Appliance Class: II

Protection

IP: 20
IK: 10