




Product data sheet

PANELTECH UGR<LT/>19 - A 4000K CRI 80 34W CLD-E WHITE
22184810-31
DISANO



Housing: body in steel sheet and frame in aluminium. Diffuser: extruded panel in high transmittance prismatic technopolymer. Internal PMMA slab. : UGR<LT/>19, according to standard EN 12464. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: Ceiling lighting fixture with external driver; it can be easily housed in false ceilings. Mounting: recessed only for surface mounting on T-beams or suspended. Easy installation: quick connection without the need to open the luminaire, can be easily inserted into the ceiling. On request: - DIMM DALI CLD-D wiring (subcode -0041) - CLD-D (PUSH) (subcode -0045)

Light output 1 (emergency)



1 x LED			
Nominal lamp power	34 W	LOR	100%
Lamp flux	3527 lm	Total flux	3527 lm
Luminous efficacy	104 lm/W	Total power	34 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 1.69 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 34 W
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 40
IK: 05
Designation labels: CE