



Product data sheet

LOUI 50
925360.002.76
RZB



Series: LESS IS MORE 50 system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Colour: traffic white, matt (RAL 9016) Length: 841 mm Width: 71 mm Height: 1.5 mm Cut-out length: 848 mm Cut-out width: 60 mm Recess height: 100 mm Luminaire: recess height: 75 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 22 W Rated luminous flux: 2500 lm Luminous efficiency: 114 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22 W	CRI	80
Total flux	2500 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	22 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.80 in
Width: 33.11 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 22 W

Protection

IP: 20
IK: 03