


Product data sheet

ALPHABET ZONO RECESSED LUMINAIRE, SOFT CARRÉ
AZ2102016-30-30 + 86009Q18_22W
SCHMITZ | WILA



alphabet zono LED 3000 K Recessed Luminaire, Light distribution direct Downlight with lite optic Soft Carré Product: AZ2102016-30-30
Operating technology: independent driver required Lite Optic: 86009Q18 The powerful LED Downlight family provides best visual comfort and protection of the reflector surface at the same time. Lite Optic Soft Carré A combination of matt and lateral clear acrylic providing definite glare limitation and an unobtrusive ceiling brightness. Integrated in a white reflector for installation into the luminaire without tools, safety suspension included. Light Technique Light-proof housing Highly efficient light chamber thanks to primary reflector with reflectance 99% Uniform illumination due to integrated diffusing screen with micro pearl technology Mirror reflector made of pure aluminium (AL99.98), high-polished ENEC-certified LED module Colour rendering index CRI>80 Constant colour temperature 3000 K Colour consistency < 3-step MacAdams (SDCM) 50,000h lifetime (L70) Luminaire housing Non deformable housing made of Aluminium and UV-resistant plastic Light-proof housing Slightly raised mounting frame for homogeneous ceiling appearance Frame colour white (comparable RAL 9016) Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 3-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Project-related solution with concrete mounting box recess depth 90mm possible Lamp Wattage: 22 W Colour Rendering Index: 80 Colour Temperature: 3000 K Luminaire Luminous Flux: 1580 Lm System Efficiency: 63 Lm/W Luminance $\gamma \geq 65^\circ$: --- UGR: 25 Number Luminaires LZ: 0.10 Connector: screw connector, 2 x 1.5 mm² Reflector Size: Q18 Length: 207 mm Width: 207 mm Cut-out length: 200 mm Cut-out width: 200 mm Installation Depth RD: 135 mm Total Weight: 2.2 kg Degree of Protection IP44, IP44 in closed ceiling systems CE-Sign Total system: Protection class 2 Data record AZ2102016-30-30+86009Q18_22W

Light output 1



1 x General service incandescent lamp

Nominal lamp power	25 W	LOR	100%
Lamp flux	1580 lm	Total flux	1580 lm
Luminous efficacy	63 lm/W	Total power	25 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 8.15 in

Width: 8.15 in

Height: 5.31 in

Adjustability

Fixed

Electric

System power: 25 W

Appliance Class: II

Protection

IP: 44

Design

Color of housing: White