

# Product data sheet


VOLICA 2.0 LED N/T 2406 6700LM 3000K OPAL MATT (PMMA) WHITE  
010481.5L07.214

LUG



Surface-mounted decorative luminaire for LED light sources; aluminum profile available in various colors, equipped with an efficient lighting system, optimized for indoor use. Mounting: surface mounted Body: aluminum profile Power supply efficiency: >87% Power: 220-240V 50/60Hz Includes light source: yes Lifetime (L80B10): 100 000 h Lifetime (L90B10): 50 000 h Warranty: 5 years Application: offices, hotels, reception desks, galleries, auditorium, boutiques, museums

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 56 W     | CRI         | 80     |
| Total flux         | 6700 lm  | LOR         | 100%   |
| Luminous efficacy  | 120 lm/W | Total power | 56 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 94.72 in

Width: 2.36 in

Height: 3.15 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 56 W

Appliance Class: I

## Protection

IP: 20

IK: 04