




# Product data sheet

BARIS 40 LED Z 1450LM PRM I KL. IP44 860MM 830 14W ANODA CO  
930904  
LENA LIGHTING



930904 BARIS 40 LED Z 1450LM PRM I KL. IP44 860MM 830 14W ANODA CO Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 14 W     | CRI         | 80     |
| Total flux         | 1450 lm  | LOR         | 100%   |
| Luminous efficacy  | 104 lm/W | Total power | 14 W   |

## Mounting mode

Pendant, Ceiling mounted

## Shape and measurements

Length: 33.86 in  
Width: 1.57 in  
Height: 2.09 in

## Adjustability

Fixed

## Design

Material impression: Matt  
Color of housing: White

## Electric

System power: 14 W  
Ballast: ECG  
Appliance Class: I

## Protection

IP: 44  
IK: 03  
Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: -13...95°F