


Product data sheet

PAREO ONE LED 3000 AREA E IP66 22 740
19.3266.0006.22
LUXIONA



Outdoor luminaire. Assembly: mounted on poles. The body material is aluminum. Colour - RAL 9007 (dark gray). Luminaire dimensions: Ø490 x 560 mm. Weight 5,55 kg. Diffuser: hardened transparent glass. Beam angle: (C0-C180) / (C90-C270) - 118,2° / 112,4°. Light source type: LED. Colour of the light 4000 K. CRI>70. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 2789 lm. Power of luminaire: 18,1 W. Luminaire's light efficiency: 154,1 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,9. Circuit load capacity: 15 (B10), 25 (B16), 25 (C10), 40 (C16). Operating temperature range: -40 ÷ 40° C. Protection degree: IP66. Impact resistant: IK09. Protection against electric shock: II.

Light output 1



1 x LED			
Nominal lamp power	18.1 W	LOR	83%
Lamp flux	3392 lm	Total flux	2831 lm
Luminous efficacy	187 lm/W	Total power	18.1 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Height: 22.05 in
Diameter: 19.29 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite, Silver gray

Electric

System power: 18.1 W
Appliance Class: II

Protection

IP: 66
IK: 09

Other operating numbers

Ambient temperature range: -40...104°F