## Product data sheet

SMART CAKE 82 LED GE 2700K MEDIUM GOLD 12411046

MODULAR









Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask or Smart surface box to form the perfect solution for any interior. What you get is a LED module with a different finish. The light flows over the edges of the Smart Cake like its bigger sister.

## Light output 1



| 1 x LED            |         |
|--------------------|---------|
| Nominal lamp power | 13.4 W  |
| Lamp flux          | 956 lm  |
| Luminous efficacy  | 63 lm/W |
| CCT                | 2700 K  |
| CRI                | 90      |


| LOR         | 88%    |
|-------------|--------|
| Total flux  | 842 lm |
| Total power | 13.4 W |
|             |        |



| IXLED              |         |
|--------------------|---------|
| Nominal lamp power | 6.2 W   |
| Lamp flux          | 554 lm  |
| Luminous efficacy  | 79 lm/W |
| CCT                | 2700 k  |
| CRI                | 90      |
|                    |         |

1 v I ED

| 88%    |
|--------|
| 488 lm |
| 6.2 W  |
|        |



| 1 x LED            |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 9.2 W   | LOR         | 88%    |
| Lamp flux          | 744 lm  | Total flux  | 655 lm |
| Luminous efficacy  | 71 lm/W | Total power | 9.2 W  |
| CCT                | 2700 K  |             |        |
| CRI                | 90      |             |        |

## Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in Diameter: 3.23 in

Adjustability

Fixed

Electric

System power: 6.2-13.4 W Appliance Class: II

Protection

IP: 20