


Product data sheet

LP CIRCLE SURFACE MOUNTED Ø260 BLACK LED 3000K 13W
5742580731
LOUIS POULSEN



LP Circle Surface Mounted Design: Mikkel Beedholm/KHR arkitekter Concept: The fixture emits diffuse light via a high-efficiency acrylic diffuser. The diffuser, which is encircled by a voluminous coloured or white ring, is hidden when viewed from low angles. Angling the inner side of the reflector ring 5° creates a comfortable and decorative graduation of the light from the diffuser. The luminaire ,floats' 34 mm below the ceiling, creating a visual lightness. Finish: White, Black, Pale Petroleum or Yellow. Powder coated. Material: Reflector: Extruded aluminium. Diffuser: Acrylic, frosted. Top: Aluminium. Mounting: Directly on ceiling. Built-in driver. Terminal strip: 5x1.5mm2. Looping: Approved, max 5x1.5mm2. Cable entries: Rear, Side-mounted. Weight: Min: 2.4 kg Max: 5.0 kg Class: Ingress protection IP20. Electric shock protection I.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	90
Total flux	1065 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	13 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 10.51 in

Width: 10.51 in

Height: 5.24 in

Adjustability

Fixed

Electric

System power: 13 W

Appliance Class: I

Protection

IP: 20