

# Product data sheet


NOMAD 4X GU10  
1020220X  
MODULAR



IP  
20


Timeless passe-partout Nomad is a classic. This refined, industrial fitting with its visible wiring is perfect for highlighting your favourite elements in your interior. The family comprises a wide range of lighting solutions. For example, the flexible arm allows Nomad to travel a certain distance.

## Light output 1



1 x LED


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	350 lm
CCT	2700 K	Total power	5.5 W
CRI	80		



1 x LED


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	100%
Luminous efficacy	71 lm/W	Total flux	389 lm
CCT	2700 K	Total power	5.5 W
CRI	80		

## Light output 2



1 x LED


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	350 lm
CCT	2700 K	Total power	5.5 W
CRI	80		



**1 x LED**


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	100%
Luminous efficacy	71 lm/W	Total flux	389 lm
CCT	2700 K	Total power	5.5 W
CRI	80		

**Light output 3**



**1 x LED**


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	350 lm
CCT	2700 K	Total power	5.5 W
CRI	80		



**1 x LED**


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	100%
Luminous efficacy	71 lm/W	Total flux	389 lm
CCT	2700 K	Total power	5.5 W
CRI	80		

**Light output 4**



**1 x LED**

Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	350 lm
CCT	2700 K	Total power	5.5 W
CRI	80		



**1 x LED**

Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	100%
Luminous efficacy	71 lm/W	Total flux	389 lm
CCT	2700 K	Total power	5.5 W
CRI	80		

**Mounting mode**

Ceiling mounted

**Electric**

System power: 22 W

**Shape and measurements**

Length: 11.02 in

Width: 8.07 in

Height: 7.48 in

Weight: 1.02 kg

**Adjustability**

Tiltable

**Protection**

IP: 20