# Product data sheet

NOMAD 4X GU10 1020220X MODULAR







IP 20

Timeless passe-partout Nomad is a classic. This refined, industrial fitting with its visible wiring is perfect for highlighting your favourite elements in your interior. The family comprises a wide range of lighting solutions. For example, the flexible arm allows Nomad to travel a certain distance.

### Light output 1




1 x LED			
Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	350 lm
CCT	2700 K	Total power	5.5 W
CRI	80		




1 x LED			
Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	100%
Luminous efficacy	71 lm/W	Total flux	389 lm
CCT	2700 K	Total power	5.5 W
CRI	80		

### Light output 2




1 x LED			
Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	350 lm
CCT	2700 K	Total power	5.5 W
CRI	80		



### 1 x LED


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	100%
Luminous efficacy	71 lm/W	Total flux	389 lm
CCT	2700 K	Total power	5.5 W
CRI	80		

# Light output 3



# 1 x LED


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	350 lm
CCT	2700 K	Total power	5.5 W
CRI	80		



# 1 x LED


Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	100%
Luminous efficacy	71 lm/W	Total flux	389 lm
CCT	2700 K	Total power	5.5 W
CRI	80		

# Light output 4



#### 1 x LED

I X LLD			
Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	100%
Luminous efficacy	64 lm/W	Total flux	350 lm
CCT	2700 K	Total power	5.5 W
CBI	80		



# 1 x LED

Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	100%
Luminous efficacy	71 lm/W	Total flux	389 lm
CCT	2700 K	Total power	5.5 W
CRI	80		

Mounting mode

Ceiling mounted System power: 22 W

Electric

# Shape and measurements

Length: 11.02 in Width: 8.07 in Height: 7.48 in Weight: 1.02 kg

# Adjustability

Tiltable

### Protection

IP: 20