

Product data sheet


ML4 LED 4" RECESSED DOWNLIGHT SYSTEM
ML4D09_940 - TIR50AWW25 - TL45R6GMWBB - TL46S6GMWBB
COOPER LIGHTING



IP
47

4" modular downlight; Downlight, wall wash, accent/task distributions, Field-interchangeable round and square 2-inch pinhole aperture trims, Open and lens apertures provide cutoff to source and glare control, 4 color temperatures: 2700K, 3000K, 3500K and 4000K CCT; CRI: 90, Die-formed steel trims; Magnetic attachment; Painted, plated finishes, Distributions: spot, narrow flood, flood and very wide flood, 120V-277V; Phase or 0-10V dimming down to 5%; Lumens: up to 900, L70 at 50,000 hours; D2W™ option from 3000K to 1850K, UL listed with Halo 4" housings; AIR-TITE™, ENERGY STAR™ certified; 5-year warranty

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11.3 W	CRI	100
Total flux	691 lm	LOR	100%
Luminous efficacy	61 lm/W	Total power	11.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.00 in
Width: 2.00 in
Height: 0.39 in

Adjustability

Fixed

Electric

System power: 11.3 W

Protection

IP: 47