Product data sheet

X-LINE SLIGHT UP&DOWN LED 4550/5200 PLX-T/PLX E 34 830 LINE-BM / L-2254MM S-1,5M
19.4426.8711.34
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 2254 x 34 x 68 mm. Diffuser: PLX-T/PLX (transparent PMMA/PMMA opal) [up/down]. The efficiency of the optical system is 75,54%. Beam angle: (C0-C180) / (C90-C270) - 99,6° / 103°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 7930,9 lm. Power of luminaire: 58,4 W. Luminaire's light efficiency: 135,8 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 8 (B10), 13 (B16), 11 (C10), 18 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	58.4 W	LOR	52%
Lamp flux	10518 lm	Total flux	5515 lm
Luminous efficacy	180 lm/W	Total power	58.4 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 88.74 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 58.4 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F