Product data sheet

SANTOS KREIS 311880.005.1 RZB





Series: Santos Kreis Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, white, powder-coated. Diffuser fastening: decorative ring with spring system. Diffuser: domed opal glass plate, frosted. Decorative ring: metal. Available Colours: brass Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 410, H 95 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 1550lm System power: 19W Beam Angle: 113° Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 21A Unified Glare Ratio: 20,3 EEC: A++

Light output 1 (integrated)

|--|--|

Lamp type Nominal lamp power Total flux Luminous efficacy

19 W 1550 lm 82 lm/W

LED

CCT

CRI

LOR

4000 K 80 100% ULOR 3% Total power 19 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.74 in Diameter: 16.14 in

Adjustability

Fixed

Electric System power: 19 W Protection IP: 20