

# Product data sheet

LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS  
V1-R4-00010-31A00-5403030 GR070/C 2.0 588X588X50 MM IP54 30W 3000K OPAL EM 1H  
VARTON




IP  
54

IK  
08

LED luminaire solution for GRILIATO ceilings with IP54. Stainless steel housing with white powder coating. Application: administrative facilities For GRILIATO suspended ceilings with special rails. Can be fixed at the level of GRILIATO cells with a height of 30, 40 or 50 mm. Length, mm: 588 Width, mm: 588 Height/depth, mm: 50 Input voltage (AC, 50Hz), V: 176...264 Power factor: 0,95 Ingress protection (IP): IP54 Impact resistance: IK08 Protection class: I AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 [https://www.varton.ru/products/ofisnoe-osveshchenie/varton-dlya-grilyato-gr-seriya-2-0/gr070-s-2-0-588kh588kh50-mm-ip54/svetodiodnyy-svetilnik-var-ton-gr070-c-2-0-588kh588kh50-mm-30-vt-3000-k-ip54-dlya-chistykh-pomeshchen\\_1/](https://www.varton.ru/products/ofisnoe-osveshchenie/varton-dlya-grilyato-gr-seriya-2-0/gr070-s-2-0-588kh588kh50-mm-ip54/svetodiodnyy-svetilnik-var-ton-gr070-c-2-0-588kh588kh50-mm-30-vt-3000-k-ip54-dlya-chistykh-pomeshchen_1/)

## Light output 1



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 1 x LED            |          |             |         |
| Nominal lamp power | 30 W     | LOR         | 100%    |
| Lamp flux          | 3450 lm  | Total flux  | 3450 lm |
| Luminous efficacy  | 115 lm/W | Total power | 30 W    |
| CCT                | 3000 K   |             |         |
| CRI                | 80       |             |         |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.15 in  
Width: 23.15 in  
Height: 1.97 in

## Adjustability

Fixed

## Electric

System power: 30 W

## Protection

IP: 54  
IK: 08