


Product data sheet

TRIANGLE 6 STREET AND AREA LIGHTING LUMINAIRES
TR-96151-EW-W40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.4 W	CRI	80
Total flux	4916 lm	LOR	100%
Luminous efficacy	131 lm/W	Total power	37.4 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.4 W	CRI	80
Total flux	4916 lm	LOR	100%
Luminous efficacy	131 lm/W	Total power	37.4 W

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 49.37 in
Width: 23.62 in
Height: 20.24 in
Weight: 18 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 74.8 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 54

IK: 07

Surface temperature: 40°C