


# Product data sheet

RECESSED DIRECTIONAL SPOTLIGHT NOVO ROUND INNER RING FLUSH-  
2005.7318 - NOVO RND DS FM CR68 LED1000-940 L 35 WH DALI  
REGENT



Recessed directional spotlight Novo Round inner ring flush-mounted, with LED, system power: 10 W, standby power 0.5 W, luminous flux of luminaire 1000 lm, colour rendering index CRI > 90, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, RG 1 - low risk, photobiological safety: the luminaire poses no danger (RG0), 230 V, 310 mA, direct light emission, housing in die-cast aluminium, with ceiling trim, white, similar to RAL 9003, with lens, 35°, operating unit included in delivery, DALI2, protection class II, ingress protection IP20 / IP44, glow wire test 650 °C, impact strength: IK 01 this product contains a light source of energy efficiency class E and EPREL registration number: 863694 Ø = 85 mm, ceiling cutout ø 68 mm up to 80 mm, ET = 81 mm, swivelling 15°

## Light output 1



1 x LED			
Nominal lamp power	10 W	LOR	100%
Lamp flux	1000 lm	Total flux	1004 lm
Luminous efficacy	100 lm/W	Total power	10 W
CCT	4000 K		
CRI	90		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 3.94 in  
Width: 3.94 in  
Height: 3.74 in  
Weight: 0.823 kg

## Adjustability

Rotatable, Tilttable

## Design

Color of housing: White

## Electric

System power: 10 W  
Appliance Class: II

## Protection

IP: 44  
IK: 01