


Product data sheet

PARIO SP 1 X 16.5W 47° 4000 K
GH1135.BUFT400EC
GHIDINI



Series of spot lights to be mounted on floor, wall, spike, tree with belt or on a pole system. Available in various sizes, rotatable and inclinable on the vertical axis, they are designed for lighting facades, small, medium and tall trees, bushes, stautes, columns and other architectural elements in general thanks to a wide range of optics and wattages. Pario comes with a series of accessories that ensure different type of mounting and beam control. The body and diffuser closure ring are constructed of high oxidation resistant aluminum alloy which is subjected to nano-bonderite treatment and finished with texturized polyester powder paint, making the product resistant to atmospheric agents and UV rays, guaranteeing maximum protection over the years. Silicone gaskets ensure maximum sealing in all operating and temperature conditions. The ultra transparent tempered sodium calcium glass diffuser ensures maximum light transmittance and is finished with a silkscreen border. All the external screws are in stainless steel.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18 W	CRI	90
Total flux	1667 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	18 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 5.79 in
Diameter: 4.13 in

Adjustability

Rotatable

Electric

System power: 18 W
Appliance Class: III

Protection

IP: 65