Product data sheet


DEFINE LED SUSPENDED LUMINAIRE S122DIP-S865D330U930-4F0-1E-UDD-A4 COOPER LIGHTING



() COOPER Ligning Solutions

Surface mount slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K and 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx, Lumawatt Pro and stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

Light output 1 (integrated)



LED	CCT	3000 K
43.5 W	CRI	90
4149 lm	LOR	100%
95 lm/W	ULOR	25%
	Total power	43.5 W
	43.5 W 4149 lm	43.5 W CRI 4149 lm LOR 95 lm/W ULOR

Mounting mode

Pendant

Shape and measurements

Length: 48.00 in Width: 2.00 in Height: 0.39 in

Adjustability

Fixed

Electric

System power: 43.5 W

Protection

IP: 47