


Product data sheet

BALLERUP MINI LED 3000K 12W
5742586832
LOUIS POULSEN



Ballerup Mini Design: C. J. Nørgaard Pedersen & P. Hougaard Nielsen Concept: The light distribution is symmetric and directed downwards. The vertical three-layer mouth-blown glass cylinder provides a soft and comfortable light on the ceiling around the fixture, as well as reducing glare for passers-by. Finish: White, powder coated. White opal glass. Material: Diffuser: Mouth-blown white opal glass. Ring: Punched steel. Mounting: Ceiling thickness: 5-32mm. Ceiling Cut-Out: Ø 105mm. Looping: Not approved. Driver hardwired to housing. For more information please look at www.louispoulsen.com. Weight: Max. 0.5kg. Class: Ingress protection IP20. Electric shock protection III low voltage. Info notes: Supplied with light source. For LED replacement kits please do contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website www.louispoulsen.com

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	80
Total flux	334 lm	LOR	100%
Luminous efficacy	22 lm/W	ULOR	12%
		Total power	15 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.53 in

Width: 4.34 in

Height: 2.05 in

Adjustability

Fixed

Electric

System power: 15 W

Appliance Class: III

Protection

IP: 20