
Product data sheet

RING 50
RG50Z-159302-HXXXO
LUX-IT




pendant mounted dir-indir LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 7 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 8 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 9 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Light output 10 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12.21 W	CRI	90
Total flux	1277 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	12.21 W

Mounting mode

Pendant

Shape and measurements

Length: 62.01 in

Width: 62.01 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 122.1 W

Protection

IP: 20

Designation labels: CE