Product data sheet


LUMINAIRES FOR EDUCATIONAL FACILITIES
V1-E0-00070-01DA3-4003040 E070 2.0 IP40 30W OPAL EM 3H DALI
VARTON



IP 40 IK 02

Luminaire for lighting pre-school, school, secondary, tertiary and other Educational facilities facilities. Meets all educational lighting requirements and standards. Stainless steel housing with white powder coating. Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 90-100 Protection class: I Mounting method: Surface mounting/recessed mounting Ingress protection (IP): IP40 Radiation angle: 120 Impact resistance: IK02 Power factor: 0,95 https://www.varton.ru/products/svetilniki-dlya-obrazovatelnykh-uchrezhdeniy/e-seriya-2-0-dlya-klassov/e070-2-0-ip40-shkola-595kh595-mm-analog-4-18/svetodiodnyy-svetilnik-varton-e070-2-0-dlya-obrazovatelnykh-uchrezhdeniy-30-vt-cri90-4000-k-vstraiva_12/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3600 lm	Total flux	3600 lm
Luminous efficacy	120 lm/W	Total power	30 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 40
IK: 02