Product data sheet

MEDICAL AND CLEANROOM LIGHTING

V1-C0-00350-20GA6-5403040 C350/UGL (1195X295 MM) 30W 4000K TEMPERED GLASS EM 1H


VARTON



IP 54 IK 08

Versatile luminaire for clean facilities. Stainless steel housing with white powder coating, tempered glass diffuser. Application: healthcare, food outlets, laboratories, washrooms. Suitable for areas with high moisture and dust protection requirements. Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ2 Protection class: I Mounting method: Surface mounting/recessed mounting Ingress protection (IP): IP54 Radiation angle: 120 Impact resistance: IK08 Power factor: 0,95 https://www.varton.ru/products/svetilniki-dlya-chistykh-pomeshcheniy/c-gl-seriya-ip54-so-steklom/c350-ugl-1195-295-68-mm-ip54-universalnye-so-steklom/svetodiodnyy-svetilnik-varton-c350-ugl-meditsinskiy-30-vt-cri90-4000-k-vstraivaemyy-nakladnoy-1195kh_1/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3600 lm	Total flux	3600 lm
Luminous efficacy	120 lm/W	Total power	30 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in

Width: 11.61 in

Height: 2.68 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 54

IK: 08