Product data sheet


URBINI LED 20W 2650LM 3000K IP66 O57 - FOR PEDESTRIAN ZONES GRAY I
130232.5L291.171
LUG



IP 66 IK 08

Professional streetlight luminaire for LED light sources. Mounting: on pillar ø60mm, on horizontal and vertical pillars, on outriggers ø60mm, with mounting bracket (included) Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0,029 m² Power supply efficiency: >89% Power: 220-240V 50/60Hz Includes light source: yes Lifetime (L90B10): 100 000 h Available on request:DALI, NTC, LLOC, 10kV surge protection Additional equipment: additional anti-corrosive protection (index extension: .985) Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: cycle paths, avenues, sidewalks, parks, parking areas, residential, public spaces, playgrounds, promenade, residential area roads Type of optics: O57 - for pedestrian zones

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	70
Total flux	2650 lm	LOR	100%
Luminous efficacy	132 lm/W	Total power	20 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 16.02 in
Width: 4.33 in
Height: 4.72 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 20 W
Appliance Class: I

Protection

IP: 66
IK: 08