


Product data sheet

MODRAS 121 L35 LE3
MOD SLIM ASYMMETRIC EMERGENCY
DEXTRA




MOD Asymmetric - 1200x150, IP40, IK08 Recessed lay-in luminaire, white powder coated steel body, combined lens and film optic asymmetric distribution. Options: LE3 - Lithium Emergency (308 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) R44 - Reacta 44, Presence & Daylight RAS - Reacta Air Wireless Presence & daylight RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence 4PM - 4 Pole panel mount 6PM - 6 Pole panel mount C83 - CRI 80, 3000K MODRS TETHER KIT - Secondary fix single drop MODRS TETHER KIT TWIN- Secondary fix twin drop MODRAS L PBK1200 - 600x150mm Plasterboard Kit

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	23 W	CRI	80
Total flux	2367 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	4%
		Total power	23 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	308 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	4%
		Total power	3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in
Width: 5.71 in
Height: 4.33 in

Electric

System power: 26 W
Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 20

IK: 08

Designation labels: CE