
Product data sheet

FLC201 [GP] IP66:LED-1/6W/3K - MAX APERTURE ANGLE
139-2750
WE-EF




we-ef

IP 66 IK 07

Profile Projector [FP] for framing applications, polygon shape. Spherical/triple flat convex lens system. Profile Projector [GP] for projection of gobos on a surface. Spherical/triple flat convex lens system. Gobo motif on request, to be ordered separately. Profile Projector [ZP] for zoom spot. Spherical/triple flat convex lens system. IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring available as variant. Glass LED lens array. Factory installed LED circuit board. LED board can be removed for upgrading. Electronic control gear (ECG) in separate driver box.

Light output 1



1 x LED

Nominal lamp power	6 W	LOR	70%
Lamp flux	670 lm	Total flux	468 lm
Luminous efficacy	62 lm/W	Total power	7.5 W
CCT	3000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Height: 1.18 in
Diameter: 1.18 in
Weight: 0.5 kg

Electric

System power: 7.5 W
Appliance Class: I

Protection

IP: 66
IK: 07