


Product data sheet

SL740SL L ECO LED MP S/C 62W 840 GR-RAL9006
8740761605431
PERFORMANCE IN LIGHTING



LED free-standing luminaire for interior, including: Steel sheet head, extruded aluminium profile post, steel sheet base, powder painted / Angle of the lamp head adjustable using a set screw / Microprismatic diffuser for efficient light diffusion, glare reduction and a high uniformity / Direct / indirect light distribution / Colour rendering index Ra > 80 / Colour tolerance according to MacAdam = 3 SDCM / VDU application suitable acc. to EN 12464-1 / Complete with flexible power cord with plug / DALI dimmable / Special colour versions available upon request

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 63 W | CRI | 80 |
| Total flux | 7947 lm | LOR | 100% |
| Luminous efficacy | 126 lm/W | ULOR | 5% |
| | | Total power | 63 W |

Mounting mode

Standing / Bollard

Shape and measurements

Length: 27.56 in
Width: 12.17 in
Height: 76.30 in

Design

Color of housing: Silver gray

Electric

System power: 63 W
Appliance Class: I

Protection

IP: 20
IK: 07