


Product data sheet

PENDANT LUMINAIRE GIRO L2 128W CRI > 80 3000K DIRECT-INDIRECT LIGHT EMISSION WHITE
2010.4752 - GIRO PEN1200-1500RPY LED16500-830 DID WH DALI
REGENT




Pendant luminaire Giro L2, with rope pendant up to 1,5 meter, cable bundled centrally "Y", can be shortened on site, with LED, system power: 128 W, standby power <1 W, luminous flux of luminaire 16500 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, 230 V, nominal current: 0.59 A, direct-indirect light emission, (80%/20%), frame in aluminium white, neat shadow gap, diffuser in polymethyl methacrylate (PMMA) 2 integral control gears, DALI2, dimmable 5-100 %, protection class I, ingress protection IP40, glow wire test 650 °C, impact strength: IK 06, this product contains a light source of energy efficiency class A and EPREL registration number: 1542698 Ø = 1200 mm, W = 66 mm, H = 77 mm, p = 1500 mm

Light output 1




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 2




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 3




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 4




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 5




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 6




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 7




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 8




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 9




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 10




1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 11



1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Light output 12



1 x LED			
Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1375 lm	Total flux	1375 lm
Luminous efficacy	129 lm/W	Total power	10.7 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 47.24 in
Width: 47.24 in
Height: 3.03 in
Weight: 16.88 kg

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 128.4 W
Appliance Class: I

Protection

IP: 40
IK: 06