
Product data sheet

LINEAR LIGHTING

V1-R0-90827-02OPA-4004027 X-LINE 2,00 M STAND-ALONE 40W 2700K EM 1H


VARTON



IP 40 IK 01

• Extruded aluminum luminaire • Standalone Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-odinochnye/x-line-2-00-m-odinochnye/svetodiodnyy-svetilnik-varton-kh-line-odinochnyy-podvesnoy-40-vt-2700-k-1995x63x100-mm-ip40-ral9005-/

Light output 1



1 x LED

Nominal lamp power	40 W	LOR	100%
Lamp flux	4100 lm	Total flux	4101 lm
Luminous efficacy	102 lm/W	Total power	40 W
CCT	2700 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 78.54 in

Width: 2.48 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 40 W

Protection

IP: 40

IK: 01