

Product data sheet

DECORATIVE LIGHTING
V1-R0-50502-20000-2004830 COSMO 600 MM SURFACE MOUNTED 48W 3000K
VARTON




IP
40

IK
03

• Round luminaire with homogenous illumination • Material: Stainless steel housing Application • Offices • Corridors • Lobbies • Reception areas • Hospitality (restaurants, hotels, coffee bars) Installation • Surface-mounted Input voltage (AC, 50Hz): 220...240 AC frequency: 50 Flicker: 5 Climatic modification and category of placement: УХЛ4 Protection class: I Housing material: Aluminium Mounting method: Surface mounting Ingress protection (IP): IP40 Impact resistance: IK03 Power factor: 0,95 https://www.varton.ru/products/intererno-osveshchenie-dekorativno-osveshchenie/cosmo/cosmo-600-mm-nakladnye-svetodiodnyy-svetilnik-var-ton-cosmo-nakladnoy-48-vt-cri90-600kh115-mm-3000-k-s-rasseivatelem-opal-ra_6/

Light output 1



1 x LED			
Nominal lamp power	48 W	LOR	100%
Lamp flux	4500 lm	Total flux	4501 lm
Luminous efficacy	94 lm/W	Total power	48 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.53 in
Diameter: 23.62 in

Adjustability

Fixed

Electric

System power: 48 W

Protection

IP: 40
IK: 03