


Product data sheet

M26L - SPY 52 SOFT 93045 DIM5
23298 9035
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M26L - SPY 52 SOFT 93045 DIM5, available in the colour(s): black, flemish bronze, flemish gold, gold coloured, white. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26L - PROFILE. This luminaire is equipped with LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: DALI. Light distributor: reflector 45°.


Light output 1




1 x LED			
Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	7 W
CCT	1800 K		
CRI	90		



1 x LED			
Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	7 W
CCT	1800 K		
CRI	90		




1 x LED			
Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	7 W
CCT	1800 K		
CRI	90		

**1 x LED**


Nominal lamp power	10.2 W
Lamp flux	1038 lm
Luminous efficacy	102 lm/W
CCT	1800 K
CRI	90

LOR	73%
Total flux	755 lm
Total power	7 W

**1 x LED**


Nominal lamp power	10.2 W
Lamp flux	1038 lm
Luminous efficacy	102 lm/W
CCT	1800 K
CRI	90

LOR	73%
Total flux	755 lm
Total power	7 W

**1 x LED**


Nominal lamp power	10.2 W
Lamp flux	1038 lm
Luminous efficacy	102 lm/W
CCT	1800 K
CRI	90

LOR	73%
Total flux	755 lm
Total power	7 W

**1 x LED**


Nominal lamp power	10.2 W
Lamp flux	1038 lm
Luminous efficacy	102 lm/W
CCT	1800 K
CRI	90

LOR	73%
Total flux	755 lm
Total power	7 W

**1 x LED**


Nominal lamp power	10.2 W
Lamp flux	1038 lm
Luminous efficacy	102 lm/W
CCT	1800 K
CRI	90

LOR	73%
Total flux	755 lm
Total power	7 W




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	7 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	7 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	7 W
CCT	1800 K		
CRI	90		



1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	7 W
CCT	1800 K		
CRI	90		



1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	7 W
CCT	1800 K		
CRI	90		

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 0.79 in
Width: 6.69 in
Height: 0.04 in

Electric

System power: 7 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE